

8.4 Extra Smart Long-Run Series (Rack) 1000VA~5000VA

General Features:

- ◆ Smart backup time estimation for any kind of battery
- ◆ Adjustable voltage sensitivity, voltage-transfer points, & charging voltage.
- ◆ Generator compatible
- ◆ Automatic restart of load after UPS shutdown
- ◆ Smart AVR function (Two buck / boost modes)
- ◆ Cold-start capable
- ◆ Audible alarm
- ◆ Hot-swappable batteries
- ◆ Network manageable (SNMP optional)
- ◆ Full function of LCD display
- ◆ Smart battery management
- ◆ Intelligent double stages of charging control, Wet battery compatible
- ◆ Thermal control cooling fan



Output

	115V Models	230V Models
Power Levels crated at nominal inputs	1000VA / 630W ; 2000VA / 1250W ; 3000VA / 1800W 4000VA / 2500W ; 5000VA / 3200W (for 230V only)	
Output Voltage	100V/110V/115V/120V Selectable	200V/220V/230V/240V Selectable
Voltage Waveform	Sine wave	
Crest Factor	3 : 1	
Output Frequency (Synchronized to Mains)	Auto Select for 50/60Hz 47Hz ~ 55Hz for 50Hz nominal; 56Hz ~ 65Hz for 60Hz nominal	
Regulation (Nominal)	±5% typical of nominal voltage (optional at ±10% AVR for wide I/P up to ±35%)	
Regulation (Battery mode)	±3% of selected output voltage (adjustable with the remote set-up software)	
Transfer time	Blackout 3ms; Brownout 1ms; Battery mode to Normal mode : 1ms typical	
Over current protection	Over load alarm level 100% ~ 120%; Over load shutdown level 120% ~ 190% (Adjustable by using the remote set-up software)	

Input

	115V Models	230V Models
Nominal Voltage	100V/110V/115V/120V Selectable	200V/220V/230V/240V Selectable
Input Frequency	47Hz ~ 65Hz, 50/60Hz auto-sensing	
Efficiency	97% (Normal mode)	
Noise Filtering	Full time EMI/RFI filtering	

Over current protection	By re-settable over current protector	
Voltage Range	-20% ~ +24% for selected nominal voltage. -29% ~ +33% adjustable by using the remote set-up software	
AVR Range (2 Bucks, 2 Boosts)	Enhanced Buck: +15% of selected nominal voltage Buck mode: +5% of selected nominal voltage Boost mode: -5% of selected nominal voltage Enhanced Boost: -12.5% of selected nominal voltage	
Surge Protection	324 Joules	1000VA ~ 3000VA : 440 Joules 4000VA / 5000VA : 660 Joules

Battery

Battery type	Lead-Acid 25Ah ~ 250Ah	
Voltage	24Vdc (for 1000VA / 2000VA), 48Vdc, & 72Vdc	
Typical backup time	No Limit	
Charging method	Smart pulse charging with two charging modes. Quick charging when battery is not fully charged, trickle charging when battery is 90% fully charged.	
Average charging current	11A at normal line and normal temperature	
Average charging voltage for each battery	Quick charging mode : 14V maximum : Trickle charging mode : 13.2V ~ 13.9V adjustable with the remote set-up software.	
Protection	Over current protection (SCR control) Over charging voltage protection (SCR control) Thermal protection (CPU control) : When temperature inside UPS is over 45°C, charger will stop charging for 2.5 minutes followed by an 1.5 minutes charging. The cycle will be repeated until the temperature is lower than 44°C.	
Monitoring	Smart monitoring & warning for failed battery or open-circuit battery. Auto-detection each time when power on or every 6 days	

Communications & Management

Standard Interface port	UPSilon2000 compatible. Standard RS232 & Optional USB.	
Optional Interface part	RJ45 (Surge protection), DB9, SNMP	
Control panel	LCD	
Audible alarm	Alarm on battery : Low battery & Battery over voltage Alarm on abnormal operation : Over load, Short-circuit, & Over heat	
EBT (Estimation of Backup Time) system	Yes	
Green mode function (Auto-shutdown during blackout)	1% to 14% of full load (adjustable by using the remote set-up software). The default setting is OFF.	
Cooling fan control	Auto on / off, controlled by temperature & operation mode	

Environmental and Safety

Operating Temperature	Up to 1500 meters : 0°C to 40°C (32°F to 104°F)	
-----------------------	---	--

Transit/storage Temperature	-15°C to 55°C (5°F to 131°F)	
Relative Humidity	5 - 95% non condensing	
Operating Altitude	0 ~ 3000 meters	
Audible noise at 1M from surface of unit	≤50 dBA	
Safety Markings	BSMI	CE
EMC	Class B, EN50091-2, FCC part15, IEC1000-2-2	
Isolation	1.5KVac for 1 minute between battery and AC side	
Quality control system	ISO 9001	
Physical		
Dimensions: (H×D×W) Unit / Shipping	1000VA ~ 2000VA : 2u x 45 (cm) / 59 x 33 x 59 (cm) 2000VA ~ 4000VA : 3u x 45 (cm) / 59 x 33 x 59 (cm) 5000VA : 4u x 48 (cm) / 64 x 40 x 60 (cm)	
Weight: Net / Gross (kg)	2u	1000VA : 26 / 30 (kg) ; 2000VA : 26 / 30 (kg)
	3u	2000VA : 26 / 30 (kg) ; 3000VA : 29 / 33 (kg) ; 4000VA : 36 / 40 (kg)
	4u	5000VA : 45 / 49 (kg)
Packing	Export carton for each unit, 16 - 30 units per pallet	